

Specifications*

MODEL	SB36m	SB36h(c)	SB50h(c)
ENGINE (DIESEL)			
Model	A1700N2	A1700N4	A1700T3
Type	Water cooled 3-cylinder diesel		Water cooled 4-cylinder diesel
Displacement (cc)	1714		2286
Engine gross power (HP/ kW)	35/ 26.2	35/ 25.7	48.0/ 35.8
Torque (Nm @ rpm)	110.0 @ 1700		155.0 @ 1650
Rated speed (rpm.)	2600		
Fuel tank capacity (l.)	27		
Combustion system	Indirect		
Battery (V.)	12		
Air cleaner	Dry, element		
TRAVELLING SYSTEM			
Transmission	SynchroMesh	Hydrostatic	
Groups	12 / 12	3	
Max. forward speed (km/h)	26.2	29.2	28.5
Drive system	4 Wheel Drive		
Brake	Wet, multidisc		
Sperddifferential	Rear		
TIRES			
Agri	Front	8-16	ROPS: 8-16 / Cabin: 7-16
	Rear	12.4-24	ROPS: 12.4-24 / Cabin: 11,2 -24
Turf	Front	27x8.5x15	27x8.5x15
	Rear	41x14-20	41x14-20
Industry	Front	10x16.5	ROPS: 10x16.5 / Cabin: 24x8.5-14
	Rear	15-19.5	ROPS: 420/70-24 / Cabin: 380/70R19.5
PTO			
Rear PTO (rpm.)	independent, 560 and 780		
HYDRAULIC SYSTEM			
Main (lpm.)	31.0	33.6	38.2
Steering (lpm.)	16.7	18.0	17.0
Pressure (bar)	180-185		
Steering category	Power Assisted Hydrostatic		
Control type	Position / Draft		
Remote Control valve (ROPS/ Cabin)	1 double acting rear / 2 double acting rear 1 float postion		
Hitch category	Cat. 1		
Max. lift capacity (kg)	1500		
DIMENSIONS			
Length (mm)	3406	3096	
Width (mm)	1324	1451	
Height (mm)	2471	2643	
Ground clearance (mm)	366	335	
Wheelbase (mm)	1670	1671	
Weight incl. ROPS (kg)	1444	1383 / 1563	1423 / 1563

*The specifications are subject to change without notice.

COMPACT TRACTOR

SB36-50

SHIBAURA



Important information

• Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.



SHIBAURA EUROPE BV
 Begonialaan 7
 NL - 6851 TE Huissen
 T. 0031 (0)26 326 9999
 F. 0031 (0)26 326 9990
 E. info@shibaaura.com
 I. www.shibaaura.com

Dealer:

DASHBOARD



Easy to read control panel with all the important information.

TIRES



Industrial-, agricultural- and turf tires

ENGINE



The 3 and 4 cylinder diesel engines delivers the highest power in its class with outstanding durability and reliability. High-quality components guarantee a long service life.

FRONT LIFT



Front lift cat. 1 with a lifting capacity of 1500 kg.



3-POINT HITCH



The category 1 hitch has a lift capacity of 1650 kg at the ball end.

PEDALS



Hydrostatic control pedals for smooth hands free forward and reverse motion.

FRONT LOADER



As an option, the tractor can be equipped with a front loader.

CABIN



High specification, factory fitted cabin with an ergonomic layout of the controls. Standard with air conditioning and radio.