

Specifications*

MODEL		SB62h(c)	SB78mc
ENGINE (DIESEL)			
Model		A2300T8	D3400
Type		Water cooled 4-cylinder diesel	
Displacement	(cc)	2286	3409
Engine gross power	(HP/ kW)	60/ 44.1	78/ 58.1
Rated speed	(rpm.)	2600	2500
Fuel tank capacity	(l.)	45	90
Combustion system		Indirect injection	Direct injection
Battery	(V.)	12	
Air cleaner		Dry element	
TRAVELLING SYSTEM			
Transmission		Hydrostatic	Mechanical
Groups		3	16 V, 16 A
Forward speed	(km/h.)	0 - 27.3	0.95 - 39.85
Drive system		4 wheel drive	
Clutch		Dry single plate	Wet, multiplate
Brake		Wet, multidisc	
Sperddifferential		Rear	
TIRES			
Agri	Front	9.5-16	11.2-24
	Rear	13.6-26	16.9-30
Turf	Front	29x12.5-15	
	Rear	44x18-20	
Industry	Front	10x16.5	
	Rear	17.5Lx24	
PTO			
Rear PTO	(rpm.)	independent: 584 and 791	independent: 540, 750 and 1000
HYDRAULIC SYSTEM			
Main	(lpm.)	42	50
Steering	(lpm.)	19	30
Steering category		Power Assisted Hydrostatic	
Control type		Position / Draft	
Remote control valve		2x double acting rear, 2x double acting front	3x double acting rear, 2x double acting front
Hitch category		Cat. 2	
Max. lift capacity	(kg)	1500	2243
DIMENSIONS			
Length (with frontweights)	(mm)	3282	4117
Width	(mm)	1625	1893
Height	(mm)	2489	2605
Ground clearance	(mm)	322	488
Wheelbase	(mm)	1806	2200
Weight	(kg)	1722 / 1968	2765

*The specifications are subject to change without notice.

TRACTOR

SB62-78

SHIBAURA



Important information

• Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.



SHIBAURA EUROPE BV
 Begonialaan 7
 NL - 6851 TE Huissen
 T. 0031 (0)26 326 9999
 F. 0031 (0)26 326 9990
 E. info@shibaaura.com
 I. www.shibaaura.com

Dealer:

DASHBOARD



Easy to read dashboard with all important information.

PTO OPERATION



Electric hydraulic independent PTO operation.

DIFFERENTIAL LOCK SYSTEM



Differential lock system improves traction on slippery surfaces with easy accessible controls.

TURNING CIRCLE



The turning angle makes it easy to maneuver in tight areas.



OPERATION LIFT ARM



The 3-point lift arm control buttons are positioned on the rear fender under the rear light.

3-POINT LIFT



A strong rear 3-point hitch (category II) with lift capacity of 2243 kg.

CONTROLS



Electro-hydraulic controls are ergonomically designed for convenient operation.

CABIN



Nicely finished, low-noise factory cabin, standard with radio and air conditioning.